



**VOLTA
BELTING**
Technology

⋮
⋮
⋮

Conveying Solutions Special Sidewalls



The Next Step in Belting

Special Sidewalls




Volta Sidewalls are manufactured from our unique homogenous TPE materials and are especially designed to be fully compatible with all our flat belts. In addition, our sidewalls are compatible with most PU belts and some PVC belts. Welding our sidewalls is very easy and keeps the belt surface smooth, boosting the hygiene levels. This product line includes three color sidewalls for the different industries - white, green and blue. Because of its homogenous characteristics, Volta sidewalls are highly resistant to cutting, tearing, oils and abrasion. Our white and blue sidewalls conform to the highest international standards for food contact.

Reasons to Use Volta Sidewalls:

- Fully compatible with all Volta flat belts
- Compatible with most PU and some PVC belts
- High resistance to cutting, tearing, oils and abrasion
- Long and reliable service life
- White (W) and Blue (MB) Sidewalls are USDA / FDA / USDA Dairy Approved, Declaration of Conformity in compliance with EU Regulations No.: 10/2011, 1935/2004 and Directive 2002/72/EC.
- Suited to HACCP standards.

VOLTA SIDEWALL STRIPS WITH BASE

- Product:** Flexible Sidewalls (SWW, SWB & SWZ)
Material: Volta FW/FMB-(FDA, USDA, 3A)
 Volta FZ (green, GenCon)
Compatibility: Volta M family Materials
 W, MW, MB, Z, G, GZ



*non standard

Type	SW - 20		SW - 30		SW - 40		SW - 50		SW - 60		SW - 80		SW - 100	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
Height : H	20	13/16	30	1 1/4	40	1 1/2	50	2	60	2 3/8	80	3 1/8	100	4
Base Width: W	40	1 1/2	40	1 1/2	40	1 1/2	70	2 3/4	70	2 3/4	70	2 3/4	70	2 3/4
Wall Width: B	18	5/7	18	5/7	18	5/7	34	1 5/16	34	1 5/16	34	1 5/16	34	1 5/16
Weight (kg/meter)	0.17		0.21		0.24		0.39		0.42		0.52		0.62	
Minimum Pulley														
Belt Thickness:	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
2	95	3 3/4	95	3 3/4	100	4	NR	NR	NR	NR	NR	NR	NR	NR
2.5	100	4	100	4	110	4 3/8	NR	NR	NR	NR	NR	NR	NR	NR
3	105	4 1/8	105	4 1/8	115	4 1/2	125	5	130	5 1/8	150	6	200	8
3.2	105	4 1/8	105	4 1/8	115	4 1/2	125	5	130	5 1/8	150	6	200	8
4	110	4 3/8	110	4 3/8	130	5 1/8	130	5 1/8	135	5 3/8	150	6	200	8
5	120	4 3/4	120	4 3/4	135	5 3/8	135	5 3/8	140	5 1/2	150	6	200	8

Remark: Given MPD Dimensions Relate to Normal Flex. For Back Flex MPD Must Multiplied By X 1.5.

The techniques for welding our Sidewalls on to the base belt remain basically unchanged. However, we recommend that you make several welding practice runs to acquaint yourself with the way the material responds.

If you have any technical questions or would like to receive more information, please contact your local Volta distributor.



Corporate Headquarters
 Sales and Manufacturing
 sales@voltabelting.com

USA
 • Tel: +1 973 276 7905
 • Fax: +1 973 276 7908
 • Toll Free: 1-877-VOLTAUS

www.voltabelting.com

EUROPE
 • Tel: +31-546-580166
 • Fax: +31-546-579508

Volta Belting makes no warranty with respect to any of its products for a particular purpose. See **Volta** General Terms and Conditions.

Copyright©2014 Volta Belting Technology Ltd.
 CAT308EN01 - Ver. C - July 2014